

**Enterprise-class,  
Layer 2 unmanaged  
switches for small and  
medium businesses**

## OVERVIEW

3Com® Baseline switches provide cost-effective Layer 2 10/100 and 10/100/1000 Ethernet switching for LANs that don't need management capabilities. Simple to install and economical to own, they feature wire-speed performance on fixed-configuration, rack-mountable platforms.

## KEY BENEFITS

### WIDE-RANGING UNMANAGED FAMILY

Small to mid-sized businesses looking for a switched LAN with or without high-speed uplinks, or a low cost, high-performance Gigabit network, will find an affordable solution with the family of 3Com® Baseline switches, designed for plug-and-play network operation.

### 10/100 SWITCHING WITH LEGACY SUPPORT

3Com Baseline Switch 2016 and 2024 are ideal for businesses with legacy Ethernet desktops that want to start a network. Fast Ethernet (100 Mbps) support easily handles higher speed desktop and office server connections.

### HIGH-PERFORMANCE 10/100/1000 SWITCHING

For top performance, the 3Com Baseline Switch 2808, 2816 and 2824 deliver wirespeed Gigabit throughput and a switching capacity of up to 48 Gbps to handle the most bandwidth-hungry applications.

### PLUG-AND-PLAY UNMANAGED OPERATION

3Com Baseline switches operate straight out of the box, with no configuration required. Auto MDI/MDIX ports identify and adapt to the Ethernet cable type, eliminating the most common cabling errors and simplifying installation. Autosensing ports detect and adjust to the speed of the connected device to optimize network performance.

### RACK-MOUNTED OR FREE-STANDING CONFIGURATION

Small-business configurations can vary, so the switches are designed to operate as a free-standing or rack-mounted switch with included mounting kit. The standard 19-inch, one rack-unit-high (1 RU) enclosure optimizes valuable office space.

### THREE-YEAR HARDWARE WARRANTY

3Com gives a Three-Year Limited Hardware Warranty on the Baseline Switch Family. Advance Hardware Replacement, with Next Business Day shipment in most regions, is also provided.



3Com Baseline Switch Family

## SPECIFICATIONS

All information in this section is relevant to all members of the 3Com Baseline Switch family, unless otherwise stated.

### CONNECTORS

#### Switch 2016

16 auto-negotiating 10BASE-T/100BASE-TX ports configured as auto MDI/MDIX

#### Switch 2024

24 auto-negotiating 10BASE-T/100BASE-TX ports configured as auto MDI/MDIX

#### Switch 2126-G

24 auto-negotiating 10BASE-T/100BASE-TX and 2 10BASE-T/100BASE-TX/1000BASE-T ports configured as auto MDI/MDIX

#### Switch 2808

8 auto-negotiating 10BASE-T/100BASE-TX/1000BASE-T ports configured as auto MDI/MDIX

#### Switch 2816

16 auto-negotiating 10BASE-T/100BASE-TX/1000BASE-T ports configured as auto MDI/MDIX

#### Switch 2824

24 auto-negotiating 10BASE-T/100BASE-TX/1000BASE-T ports configured as auto MDI/MDIX

### MEDIA INTERFACES

10/100/BASE-TX RJ-45 or 10/100/1000BASE-T RJ-45, depending on model

### PERFORMANCE

Wirespeed performance across all ports

Store-and-forward switching

### LAYER 2 SWITCHING

MAC addresses:

- Switch 2016, 2024 and 2126G– 4,000
- Switch 2808– 8,000
- Switch 2816 and 2824– 32,000

Auto-negotiation of port speed and duplex

IEEE 802.3x full-duplex flow control

### CONVERGENCE

(Switch 2808, 2816 and 2824 only)

4 hardware queues per port

IEEE 802.1p Class of Service/Quality of Service (CoS/QoS) on egress

### LED INDICATORS

Link status/speed, duplex status, power

### POWER SUPPLY

Input voltage: 100-240 VAC, 50/60 Hz

Current rating: 1A, max.

Power inlet: IEC 320

Power consumption, max:

- Switch 2016– 15W
- Switch 2024– 20W
- Switch 2126-G– 13 W
- Switch 2808– 28W
- Switch 2816– 37W
- Switch 2824– 46W

Power dissipation, max:

- Switch 2016– 52 BTU/hr
- Switch 2024– 68 BTU/hr
- Switch 2126-G– 43 BTU/hr
- Switch 2808– 96 BTU/hr
- Switch 2816– 125 BTU/hr
- Switch 2824– 156 BTU/hr

### DIMENSIONS

Height: 4.4 cm (1.7 in or 1 RU)

Width: 44.0 cm (17.3 in)

Depth: 17.3 cm (6.8 in)

Weight:

- Switch 2016, 2024 and 2808– 1.5 kg (3.1 lb)
- Switch 2126-G– 1.6 kg (3.6 lb)
- Switch 2816– 1.9 kg (4.1 lb)
- Switch 2824– 2.0 kg (4.3 lb)

### ENVIRONMENTAL REQUIREMENTS

Operating temperature: 0° to 40°C (32° to 104°F)

Operating humidity: 10 to 95% (non-condensing)

Standard: EN 60068 (IEC 68)

### REGULATORY AND AGENCY APPROVALS

#### Safety

UL 1950 (Switch 2016 and 2024)  
UL/CUL 60950-1 (Switch 2126-G, 2808, 2816 and 2824 only)

CSA 22.2 950 (Switch 2016 and 2024)

CSA 22.2 60950 (Switch 2126-G, 2808, 2816 and 2824 only)

EN 60950

IEC 60950

#### Emissions

EN 55022 Class A, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, AS/NZS 3548 Class A

CNS 13438 Class A

(not applicable to Switch 2126-G)

Environmental: EN 60068 (IEC 68)

Immunity: EN 55024

### IEEE STANDARDS SUPPORTED

IEEE 802.1d MAC Bridges

IEEE 802.1p Priority Tags (Switch 2808, 2816 and 2824 only)

IEEE 802.3 Ethernet

IEEE 802.3ab Gigabit Ethernet (Switch 2126-G, 2808, 2816 and 2824 only)

IEEE 802.3u Fast Ethernet

IEEE 802.3x Flow Control

IEEE 802.3z Gigabit Ethernet (Switch 2126-G, 2808, 2816 and 2824 only)

ISO 8802-3

### PACKAGE CONTENTS

Switch unit, power cord, 4 self-adhesive rubber pads, rack-mount kit, one user guide, warranty flyer

### WARRANTY AND OTHER SERVICES

Three Year Limited Hardware Warranty, including fans and power supply

Limited Software Warranty for 90 days

Advance Hardware Replacement with Next Business Day shipment in most regions

90 days of telephone technical support

Refer to [www.3com.com/warranty](http://www.3com.com/warranty) for details.

## ORDERING INFORMATION

### PRODUCT DESCRIPTION

PRODUCT DESCRIPTION	3COM SKU
3Com Baseline Switch 2016	3C16470
3Com Baseline Switch 2024	3C16471
3Com Baseline Switch 2126-G	3C16472
3Com Baseline Switch 2808	3C16477A
3Com Baseline Switch 2816	3C16478
3Com Baseline Switch 2824	3C16479

Visit [www.3com.com](http://www.3com.com) for more information about 3Com secure converged network solutions.

3Com Corporation, Corporate Headquarters, 350 Campus Drive, Marlborough, MA 01752-3064

3Com is publicly traded on NASDAQ under the symbol COMS.

Copyright © 2007 3Com Corporation. All rights reserved. 3Com and the 3Com logo are registered trademarks of 3Com Corporation. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, 3Com does not accept liability for any errors or mistakes which may arise. Specifications and other information in this document may be subject to change without notice. 400838-007 03/07

